



Awning/Marine/Banner Fabrics

Technical Specification

Composition	: 100% Solution Dyed Woven Acrylic	Water Repellent	: Yes (Test: AATCC 127-1985)
Mildew Resistant	: Yes. (Test: AATCC30)	Opaque	: Yes
Warp	: 76 ends/inch. Yarn Count: 20/2	Sewn-in insert Fabric	: Yes
Abrasion Resistant	: Yes > 20000 cycles (Test: ASTM D 1966)	Pressure Sensitive Vinyl	: Yes
Fill	: 38 ends/inch. Yarn Count: 20/2	Translucent	: Yes
Finished Weight	: 305 g/sq.m (9.0 Oz/Sq. yard)	Breadth able	: Yes
Tensile Strength (grab)	: Warp: 337 Lbs, Fill: 208 Lbs (Test: ASTM D 5034)	Finished Widths	: 32", 47", & 60"
Tear Strength (tongue)	: Warp: 13.8 Lbs, Fill: 9.4 Lbs (Test: ASTM D 2261)	Silk Screening	: Yes.
Water Column	: >300mm (>12") (Test: UNI 5122)	Hand Painting	: Yes
Color Fade Resistant	: Yes 7/8 -8 degree solution dyed colors (UNI 7640)	Heat Sealed insert Fabric	: Yes.
Stretch Factor	: Warp 0.3%, Fill: 0.3% (Test: ASTM D 3107)	Heat Sealable	: Yes with a seam tape.
UV Resistant	: Yes: 1500+ Hours (Xenon Weather meter)	Heat Transfer Films	: Yes
Stain Repellent	: Yes Protective Fluorocarbon finish	Standard Put Up	: 60 yds per roll.
UV Protection	: Rated Excellent (Test: AS/NZS 4399:1996)	Uses	: Awnings, covers, etc.
Wetting – No droplet saturation	: 100. (Test: AATCC-22-1996)	Warranty	: Yes 5 Years*

Mailing Address

P.O. Box 1139
Ladson, SC 294456

Location Address

Ladson Business Center
3525 Iron Horse Drive Unit #106
Ladson, SC 29456

Phone

+1-866.828.7326
+1-843.408.4852

Fax

+1-866.547.4960
+1-843.285.2365