



Furniture Fabrics

Technical Specifications

Composition	: 100% Solution Dyed Woven Acrylic	Water Repellent	: Yes (Test: AATCC 127-1985)
Mildew Resistant	: Yes. [Test AATCC 30]	Opaque	: Yes
Warp	: 72 ends/inch. Yarn Count: 20/2 [Test : UNI 8099/80]	Sewn-in insert Fabric	: Yes
Abrasion Resistant	: (Wyzenbeek 9000 cycles .) Rating: Light duty.[ASTM D3597]	Pressure Sensitive Vinyl	: Yes
Fill	: 32 ends/inch. Yarn Count: 20/2 [Test : UNI 8099/80]	Translucent	: Yes
Finished Weight	: 261 g/sq.m(7.75Oz/Sq.Yard)	Breadth able	: Yes
Tensile Strength(grab)	: Warp: 331 Lbs, Fill: 121 Lbs [Test: ASTM D 5034]	Finished Widths	: 54* (137cms)
Tear Strength(tongue)	: Warp: 19.1 Lbs, Fill: 15.4 Lbs [Test: ASTM D 2261]	Silk Screening	: Yes.
Water Column	: >22 cm (>8.8*) [Test: AATCC 127 –Option 1]	Hand Painting	: Yes
Color Fade Resistant	: 7/8-8 degree solution dyed colors [UNI EN ISO 105-B04]	Heat Sealed insert Fabric	: Yes.
Stretch Factor	: Wrap 0.3%, Fill: 0.3% (Test: ASTMD 3107)	Heat Sealable	: Yes with a seam tape.
UV Resistant	: Yes: 1500+Hours (Xenon Weather meter)	Heat Transfer Films	: Yes
Stain Repellent	: Yes. Protective Fluorocarbon finish.	Standard Put Up	: 60 yds per roll.
UV Protection	: Excellent [Test: AS/NZS 4399:: 1996]	Uses	: Cushions, Umbrellas.etc.
Wetting – No droplet saturation	: 100. (Test: AATCC-22-1996)	Warranty	: Yes 3 Years*

Flammability :

1. Passes the requirements of California 117 Section E.
2. Passes the requirements of UFAC-Fabric, Class-1.

Mailing Address

P.O. Box 1139
Ladson, SC 294456

Location Address

Ladson Business Center
3525 Iron Horse Drive Unit #106
Ladson, SC 29456

Phone

+1-866.828.7326
+1-843.408.4852

Fax

+1-866.547.4960
+1-843.285.2365